



BARNES™
MOLDING SOLUTIONS

HOT RUNNER TECHNOLOGY

19 Nozzle Series

Product Catalog






Table of Contents

Hot Runner Technology	3
General Description of the Nozzle	3
General Description of 19 Nozzle Series	3
Target Group	3
Applied Standards and Norms	3
Tolerances and Customer Graphics	3
Bolt Down Manifold	4
Nozzle Tips and Schematic View S19 and SE19	5
Available Actuator PS 48.2 pneumatic	6
Cutout Dimensions MSN-19-50	7
Contact	8
Copyright	8
Patents	8



Hot Runner Technology

This catalog gives an overview of the latest product, including descriptions, dimensions and technical data. The text next to the graphics gives additional instructions on the use of the product. If available, options are explained with pictures and text. All available accessories for this product are specified. Where necessary, a separate chapter gives the information and important technical data.

General Description of the Nozzle

Hot runner nozzles are the connection to the cavity. They either gate directly into the part or into a sub runner which will feed into the cavity.

General Description of 19 Nozzle Series

This is a standard Molding solutions Nozzle.

Target Group

The target groups of this product catalog are mold designers, toolmakers, molders and service technicians. They will find the needed information in the relevant chapters.

Applied Standards and Norms

- DIN EN IEC/IEEE 82079-1 Edition 2 Creation of usage information for products
- Standard and norms for Technical drawings

Tolerances and Customer Graphics



The product catalog gives a general information about the product. For tolerances and other details, use the customer drawings. There you find the detailed information.



Illustrations simplified, schematically drawn and not to scale. All dimensions in mm.

Bolt Down Manifold

The following picture shows the standard design, components and dimensions.



*



Hot Runner Plate height depending to H_1 .





Illustrations simplified, schematically drawn and not to scale. All dimensions in mm.

Nozzle Tips and Schematic View S19 and SE19

The following Nozzle Tip Styles are available.

Valve gate - Straight pin		
Tip Style with Description	Picture	Gate diameter
S19 Standard		Ø 1,0 Ø 1,2 Ø 1,5 Ø 1,8 Ø 2,0
SE19 Special Execution		Ø 1,0 Ø 1,2 Ø 1,5 Ø 1,8 Ø 2,0

Schematic view of S19 and SE19 and Technical Data.



MSN-19-50-S19			
H ₀	H ₁	Code	DTE Watt
079	59	MSN-19-50-S19-079	400 W
104	84	MSN-19-50-S19-104	400 W
129	109	MSN-19-50-S19-129	500 W

MSN-19-50_A-SE19			
H ₀	H ₁	Code	DTE Watt
079	59	MSN-19-50_A-SE19-079	500 W
104	84	MSN-19-50_A-SE19-104	500 W
129	109	MSN-19-50_A-SE19-129	500 W
154	134	MSN-19-50_A-SE19-154	500 W
179	159	MSN-19-50_A-SE19-179	500 W
204	184	MSN-19-50_A-SE19-204	600 W
229	209	MSN-19-50_A-SE19-229	600 W
254	235	MSN-19-50_A-SE19-254	600 W

Example nozzle code: **MSN-19-50-S19-154**

Tip style (S19 - SE19)


Nozzle length



Illustrations simplified, schematically drawn and not to scale. All dimensions in mm.

Available Actuator PS 48.2 pneumatic

The following standard actuator is available. Other actuators can be used on request.



Technical Data




Pressure:
6 bar (87 psi)
Min/Max Close Forces:
F open max = 1347 N
F close max = 1415 N
Stroke:
12 mm



Illustrations simplified, schematically drawn and not to scale. All dimensions in mm.
Dimensions for reference only. Reference system drawing for complete dimensions prior to machining gate detail in mold.

Cutout Dimensions MSN-19-50

The following pictures shows the cutout dimensions for this nozzle.



Abbr.	Written out
Dg	Gate Diameter
Zvh	Cylindrical Gate height



Contact

Here you will find the main contact from Männer.

Europe / Germany

Otto Männer GmbH
Unter Gereuth 9–11
79353 Bahlingen a.K.

Tel. :+49 (0) 7663 609-0
Fax :+49 (0) 7663 609-299

Internet: www.maenner-group.com
Email: info@maenner-group.com

Copyright

All text and pictures contained herein are the property of Männer.

Copyright © 2025 Männer.


Patents

Note the copyright protection reminder pursuant to DIN ISO 16016. The specified patents are the property of Otto Männer GmbH. Their distribution and dissemination is permitted only subject to approval.

The products are protected by US, CA, CN, JP and European Community patents published on WEB. Property of Otto Männer GmbH. Not for third parties without written permission.



BARNES™
MOLDING SOLUTIONS



Barnes Molding Solutions is the expert cluster for molds, hot runners, and controls for industrial plastic injection molding. Our brands Foboha, Männer, Synventive, Thermoplay, Priamus and Gammaflux are leaders in their field. We have a comprehensive and in-depth understanding of the automotive, medical, packaging and electronics industries. We support our customers with sophisticated high-performance technologies through to customized turnkey solutions.



barnesmoldingsolutions.com

Synventive®
molding solutions

THERMOPLAY®
HotRunner-Systeme

männer®
SOLUTIONS FOR PLASTICS

FOBOHA®

PRIAMUS®

Gammaflux®